

Low-Profile  
Semi-Automatic  
Stretch Wrap Machine



## HANDLE-IT® SA Series

Model 600  
Model 800  
Model 800XHT  
Model 850PS  
Model 850PSXHT

# Model 1100AC

Model 1200UL

Part Number: SWM-SA-1100AC



**Full Set of Functions & Options**

**Power Pre-Stretch Carriage**

**Auto-Cutoff Standard!**

### Technical Specifications

Max Wrap Height	86" w/ overwrap, 94" max
Turntable Diameter	59"
Max Pallet Size	48" x 80" (93" Diagonal)
Turntable Height	3"
Weight Capacity	4,400 lbs
Pre-Stretch	250% Powered
Power Supply	110V, 10 Amp
Total Machine Footprint	105" long x 60" wide
Machine Weight	900 lbs
Turntable Speed	12 RPM

## Handle-It® Model 1100AC

The Handle-It® Model 1100AC offers top-of-the-line functions and features at a great price. It is ideal for those who are looking for an efficient machine capable of handling high volumes of pallets per day.

Standard features on the 1100AC include auto film cutoff, 250% powered pre-stretch, user-friendly PLC control panel, braked turntable, and many other elements cleverly designed to make this unit a must-have in any facility looking to improve and streamline their packaging operations.

www.handleitinc.com  
Ph: 800-236-1080

**HANDLE-IT®**

# HANDLE-IT®

## Semi-Automatic Stretch Wrapper

### Product Features

- Auto Film Cut at the end of the cycle-improving throughput
- Brushless AC motors
- Photocell for pallet height detection or custom set height
- Stop at home position
- 3 working modes: semimanual, semiautomatic, or fixed height
- Acoustic warning at the cycle start and stop
- On-board diagnostics
- Wrapped pallet counter
- Braked turntable at end of cycle
- 3 year warranty



**Digitally controlled power film pre-stretch** (250% standard) for dynamically controlled film efficiency and improved load containment, both lowering consumable cost and keeping your product safe and secure



### Responsive and user friendly PLC controls:

- Fully customized wrap cycles
- Up to 32 programmable cycle recipes
- 6 quick select buttons for quick navigation
- Over 50 different parameters with variable film tension and speed controls

**USB port** allows upload and download of data with statistic reporting and system diagnostics

**Durable Construction** with heavy gauge tube steel, 8 heavy duty support rollers, and chain drive system for rugged reliability



### Available Options

- Integrated Scale
- Remote Control
- Film usage diagnostics
- Loading Ramp
- Top Press
- Auto attach and wipe
- Roping System
- Photocell for Dark Loads
- Adjustable Power Pre-Stretch up to 600%
- 118" Max Wrap Height
- Cold Environment Kit