

# HANDLE-IT<sup>®</sup> SA Series



Part Number: SWM-SA-1100AA-C

### Auto Film Attach, Hot Weld Seal, Cut, & Film Tail Treatment

**Power Pre-Stretch Carriage** 

**Remote Control Operation** 

oecifications
86" with overwrap 94" max
59″
48″ x 80″ (93″ Diagonal)
3″
4,400 lbs
250% Powered
110V, 20 Amp
105″ long x 60″ wide
1300 lbs
12 RPM

### Handle-It<sup>®</sup> Model 1100AA-C

The Handle-It<sup>®</sup> *Model 1100AA-C* offers top-of-the-line functions and features at a great price. It is ideal for those who are looking for an efficient machine capable of handling high volumes of pallets per day.

Standard features on the *1100AA-C* include auto film attach, cutoff, and tail treatment. Remote control operation. 250% powered pre-stretch, user-friendly PLC control panel, braked turntable, and many other elements cleverly designed to make this unit a must-have in any facility looking to improve and streamline their packaging operations.



## HANDLE-IT® Semi-Automatic Stretch Wrapper

### **Product Specifications**

- User-friendly PLC control board •
- Automatic cycle for film attach & cold cut, hot seal •
- Air device for film tail treatment
- Frequency controller for carriage and/or turntable speed adjustment •
- Photocell for pallet height detection
- Password Protection •
- Stop at 0 position
- Easily adjustable parameters such as bottom wraps, top wraps, carriage ascent & descent speed, film tension, & starting wrap height
- Quick selection of 6 main parameters or saved programs .
- USB port to upload software and download settings, reports, and statistics
- 6 working cycles: ascent/descent, topsheet, only ascent, only descent, layers, and stack •
- 3 working modes: semimanual, semiautomatic, or fixed height
- Storage of 32 end user programs •
- Acoustic warning a the cycle start and stop •
- **On-board diagnostics** •
- Braked turntable at end of cycle •
- 59" diameter turntable loading surface •
- Up to 12 RPM turntable speed •
- 4,400 lb maximum load weight •
- 48" x 80" (93" diagonal) maximum pallet size \*ensure area is clear for over-swing\* •
- Up to 250% film pre-stretch with electronic power pre-stretch motor



### **Available Options**

- **Integrated Scale**
- Loading Ramp
- Adjustable Power Pre-Stretch up to 600%
- 118" Max Wrap Height

Carriage



\*Requires 90 psi 8 gallon min. air supply

- Top Press
- Photocell for Dark Loads
- **Cold Environment Kit**









**Power Pre-Stretch**